

# TF1 Total Filter Flushing Adapter

## 59980

- Easy flushing with connection via the Fernox Total Filter TF1
- Provides full flow rate to optimise cleaning efficiency
- Fernox TF1 Flushing Adapter is rated to 85°C and fully acid resistant



For use with a Powerflow Flushing Machine, this universal adapter allows for easy connection to a heating system via a Fernox Total Filter, and provides full flow rate to optimise cleaning efficiency. The TF1 Flushing Adapter uses the same fixings and valves as the 22mm or 28mm Fernox TF1 Total Filter.

### Application

1. Close the isolating valves on the Fernox TF1 Total Filter and remove from system, leaving the valves in place.
2. Using either the original rubber seals, or replacement seals provided with the Fernox TF1 Flushing Adapter, fit in place of the filter as shown in the diagram.
3. Connect your Powerflow Flushing Machine to the Fernox TF1 Flushing Adapter. Use only PLASTIC (PP) ¾" female nut liner and seals, as provided with the Fernox Powerflow Flushing Machine and Fernox TF1 Flushing Adapter. Secure these to the hoses with screw clamps.

Spare parts for the Fernox TF1 Flushing Adapter are available.

### Package, Handling & Safety

Individually packaged with instructions included. No special storage requirements.

### Specification

When used appropriately, the Fernox TF1 Total Filter Flushing Adapter is maintenance-free.

**Single Item**

Height mm	103
Width mm	140
Depth mm	140
Weight kg	0.310
Barcode EAN	5014551599802

**Outer Carton**

Outer Height mm	440
Outer Width mm	580
Outer Depth mm	508
Outer Weight kg	16.000
Transit Type	CP1 1200 x 1000
OCU Barcode	N/A

**Last modification** 18-02-2021 (d/m/y)